

ADVANTECH ALRES

YUNO II

Universal multi-configuration integrated system

Robust, yet compact and stylish POS system

YUNO II is a new generation of the YUNO POS system ; robust, stylish and compact, it suits the many applications of the POS vertical sectors.

A fanless, flexible and high-performance hardware, it offers a choice between 3 different INTEL 11th generation processors (Tiger Lake & Elkhart Lake) ; the system is available in 2 formats (traditional 4:3 15.1" screen and Wide 16:9 15.6" screen with Full HD) and equipped with a shock- and scratch-proof, multi-touch, projected, capacitive screen (10 point PCAP technology).

Very flexible, YUNO II is available with VESA fixings options (for wall or pole mounted solutions).

The standard version features a NVMe-M.2 flash disk and stands up to dirt in the toughest settings (fat, crumbs, dust, splashes and leftovers in kitchens, restaurants and bakeries). It integrates energy efficient processors (J6412, or i3-1115G4E, or i5-1145G7E) and a heat-dissipating aluminium



structure, ensuring compliance with environmental standards (low carbon footprint).

YUNO II is an accessible product whose many features (technology, ergonomics, flexibility and design) make it good value for money. It constitutes a sensible, cost effective and long-term POS IT investment.



intel. partner ^{Titanium}



YUNO II

11th generation of INTEL processors (J6412, i3-1115G4E, i5-1145G7E) (Energy efficient processors for low carbon footprint) SSD 2 slots Projected, capacitive, multi-touch screen (10 point - PCAP) 4:3 or 16:9 formats (15.1" or 15.6") RAM 4 or 8 GB (standard) - up to 32 GE Tilting base: 0-90° Discreet yet easily accessible connectivi 2nd screen output Available with VESA bracket option(s), for Thiner base for a light design Detachable magnetic rear cover (easy a

Resistant and accessible on/off button

Transparent status LED lighted AURES

Easy maintenance (the most compact n

White Cover

2 LAN port (1 LAN port on model with J6











5.6")	
to 32 GB	
connectivity	
ption(s), for wall and pole mounter	rreplace) of the base (green / red) narket) VUNO 11 INTEL Elkhart Lake J6412, Tiger Lake i3-1115G4E or i5-1145G7E (fanless) DDR4 - 8GB standard (up to 32GB) NVMe PCIe 3.0 x 4 Standard : 1 x 256GB (up to 512GB) NVMe PCIe 3.0 x 2 / SATA M.2 15" TTF (1024 x 768) or 15.6" (1920 x 1080) (wide format in full HD) LED back-lighting Flat, zero bezel & multi-touch screen with projected, capacitive panel (10 point PCAP) 15" 400 cd/m ² , 15.6" 450 cd/m ² 2 x serial ports (RJ50 connector) 6 x USB 3.0 2 x USB 3.0 2 x USB 3.0 2 x USB 5.0 2 x to/100/1000Base-T (1 x LAN for J6412 model) Port with support for HDM, DVI and VGA (via USB-C) 24/12 V DC Internal loudspeaker + external 19v. DC on all boards CE/FCC Class B, UL, RCM, UKCA on I5 version 0 -35 "C Dust- and splash-proof Black (grey base) Polycarbonate (cover) + aluminium (structure) 50.000 hours 342.9 x 167.5 x 303.8 mm (15.1" format, with vertical screen) 382 x 170.5 x 276.1 mm (15.6" Vide format) 5.5 - 6.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 6.5 - 7.5 kg depending on the option (15.1" format) 7 for combined reading of MSR and RFID (high and low frequences), Bluetconto (BLE), NFC
er (easy and quick to remove/rep	lace)
ff button	
	on the left side of the base (green / red) erboard in the market) ?processor) VUNO II INTEL Elkhart Lake (j6412, Tiger Lake (3-1115G4E or i5-1145G7E (fanless) DDR4 - 668 standard (up to 32G8) NVMe PCIe 3.0 x 4 Standard (1 x 256G8 (up to 512G8) NVMe PCIe 3.0 x 2 / SATA M.2 15"FTF (1024 x 786) or 15.6" (1920 x 1080) (wide format in full HD) LED back-lighting Flat, zero bezel & multi-fouch screen with projected, capacitive panel (10 point PCAP) 15" 400 cd/m², 15.6" 450 cd/m² JTPUT PORTS 2 x serial ports (RJ50 connector) 6 x US8 3.0 2 x US4C (1 to CPU) 2 x 10/100/1000Base-T (1 x LAN for J6412 model) Iay Port with support for HDMI, DVI and VGA (via USB-C) 2 4/12 V DC Internal Ioudspeaker y + external I9v. DC on all boards NEOUS CEFCC Class B, UL, RCM, UKCA on IS version mgrerature 0-35 C Dust- and splash-proof Black (grey base) Polycarboate (cover) + aluminium (structure) N
1	(et)
del with J6412 processor)	
MODEL	YUNO II
Processor(s)	INTEL Elkhart Lake J6412, Tiger Lake i3-1115G4E or i5-1145G7E (fanless)
RAM	-
1 st SSD	•
SSD 2 nd slot	
LCD	
	or 15.6‴ (1920 x 1080) (wide format in full HD)
Touchscreen	
Brightness	15" 400 cd/m², 15.6" 450 cd/m²
INPUT-OUTPUT PORTS	
Serial	2 x serial ports (RISO connector)
USB	•
050	
LAN	, ,
External display	
Cash Drawer	
Audio	
Power Supply	
TPM2.0	on all boards
MISCELLANEOUS	
EMI	CE/ECC Class B. UI, RCM, UKCA
VPRO	
Operating Temperature	
Front	
Colour	
Materials	
MTBF (screen)	
Dimensions (W x D x H)	382 x 170.5 x 276.1 mm (15.6" Wide format, screen vertical)
Weight	6.5 - 7.5 kg (15.6" Wide format)
Compatible OS	Windows 10 IoT Enterprise, Windows 11, Linux, Android X86
OPTIONAL EXTRAS	
Multi-Technology Card Reader	
Addimat and/or Dallas readers	1 slot, at right of EPOS terminal
Bare-code scanners	1D & 2D
Fingerprint reader	Yes
Customer display	20 characters x 2 lines LCM
2 nd screen (touch or non touch)	10.1" - 16:9 1280 x 800
WIFI	
VESA fixings option(s)	
Anti-glare touch screen	- Provide a second
White Cover	

