

capture®

STINGRAY

15-Inch POS System




Specifications

CPU	Intel® Celeron® Elkhart Lake J6412 Processor Intel® Tiger Lake Core™ i3-1115G4 Processor Intel® Tiger Lake Core™ i5-1135G7 Processor	
Memory	1 x DDR4 SO-DIMM slot, Max up to 16GB (J6412) 2 x DDR4 SO-DIMM slot, Max up to 64GB (Tigerlake i3, i5)	
Storage	1 x M.2 2242, Mox up to 512G (J6412) 1 x M.2 2242, 1 x 2280 PCIE, Mox up to 512G (Tigerlake i3, i5)	
Power	60W-120W (24V) external adaptor	
Display	15" TFT-LCD, Pcap touch, 1024 x 768, 400 nits	
Weight	4 Kgs	
Dimensions	340 x 294 x 175mm (W x H x D)	
Audio	2 x 2W speaker	
OS	Windows 10 lot (J6412, Tigerlake)	
Environment	Operating : 0°C - 40°C, 20% - 80% RH Storage -20°C - 60°C, 10% - 90% RH	
I/O	J6412 1 x 24V DC-IN (Mini DIN) 1 x Power Button 3 x COM, RI/5V/12V (RJ45) 3 x USB3.0 (Type A) 1 x USB2.0 (Type A)	1 x 12V/24V Cash Drawer (RJII) 1 x Video Port 1 x Giga LAN (RJ45)
	Tigerlake 1 x 24V DC-IN (Mini DIN) 1 x Power Button 3 x COM, RI/5V/12V (RJ45) 4 x USB3.0 (Type A) 1 x 12V/24V Cash Drawer (RJII)	1 x Video Port 1 x Giga LAN (RJ45)
Option I/O	SKU1 1x Power USS 12V + 2x USB 2.0 SKU2 1x Power USS 24V + 2x USS 2.0	




MSR



MSR/Rfid



LCM



10.1" 2nd monitor



Contact your local EET sales representative for more information.

capture.