## GLORY

EV8626 Banknote counter

Glory's EV8626 banknote counter reduces operational processing times with superb accuracy for low to medium volumes of currency. Feed efficiency and note counting accuracy is maximised with our dependable Ultra Feed and Mechanical Double Detection technology, irrespective of note design and quality of condition.



# With a throughput of up to 1,500 notes per minute, the EV8626 offers superb operational performance saving you valuable time and money.

### EV86-Series technology

The EV8626 is a member of the EV86-Series of currency counters incorporating many of the same elements of the premium EV8650 model whilst providing the user with the correct level of functionality to meet their requirements.

### Ultra Feed

The EV86-Series incorporates Ultra Feed technology which maximises the feed efficiency of the counter, ensuring that the counter feeds all banknotes irrespective of design and quality of condition.

### **Mechanical Double Detection**

"Right First Time" count accuracy, every time.

In field tests the unique MDD system is up to 100 times more accurate than alternative systems such as opacity. MDD accurately counts all banknotes irrespective of design and quality of condition, without operator or service technician adjustment.

MDD is unaffected by

- Currency sets with different densities of paper for different denominations
- · Banknotes with excessive levels of dirt or staining
- Clear windows commonly found in polymer notes

### Speed – fast and efficient throughputs

With a top speed of 1500 notes per minute, the EV8626 offers speed and throughput levels more commonly reserved for the premium machines. The high speed, superior feed technology and "right first time accuracy" ensures that the user achieves maximum efficiencies thereby saving valuable time and money.

Speed range	600 – 1500 notes per minute
Document size range	50 × 100 mm to 90 × 185 mm
Capacity	Feed Hopper: 500 notes Output Stacker: 200 notes
Display	LCD, Count – 5 digits / Batch – 3 digits
Dimensions (H × W × D)	265 × 300 × 263 mm
Weight	7.5 kg
Power supply	98 – 264V AC, 50/60 Hz
Power consumption	150W
Manufacturing standards and approvals	ISO9001, CE, UL, GOST

\*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

### Related solutions...

### **EVOLUTION REMOTE DISPLAY**

A dependable and affordable display with a compact design to be positioned in multiple configurations.



### MACH™ 3

A versatile and compact solution, the Mach 3 will simplify coin processing for any business.



### **PROFESSIONAL SERVICES**

Transaction analysis, connectivity, advisory services, user training through to full project management.



### Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK

### 🛣 +44 (0)1256 368000 🛛 info@uk.glory-global.com 🕀 glory-global.com

DS-EV8626-0417\_2.0

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or licence save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY is a registered trademark of GLORY LTD. in Japan, the United States of America, and EU. All trademarks are owned by the GLORY Limited Group of companies. © Glory Global Solutions (International) Limited 2017.