SUNMI L2H Smart Mobile Terminal

Powerful PDA, higher, stronger and safer.

Octa-core Processor And SUNMI OS

With an octa-core processor inside and the 11nm manufacturing process adopted, L2H has been greatly improved in performance. The new SUNMI OS also brings you better design, smoothness and security.

Inbuilt Dual-band GPS And Barometer

Minimized position deviation. Locate your staff more accurately to a specific floor with the horizontal and vertical positioning system.

Barcode Reading And OCR*

In addition to reading 1D/2D barcodes (even if scratched, folded or stained), L2H also can recognize printed text with its OCR-enabled scanner.

*SUNMI provides you OCR SDK interfaces for quick and efficient OCR realization.

More Rugged And Durable

Featuring IP67 and 1.5m drop spec, L2H can stand harsh work environments with no compromise in performance.

Fingerprint Lock

Newly added fingerprint lock to protect your data.

*SUNMI provides you OCR SDK interfaces for quick and efficient OCR realization.





SUNMI L2H Tech Specs

Product Model

T8911

ns

SUNMI OS (*based on Android 11)

Processor

Kyro-260 Octa-core (Ouad Core. 2.0GHz+Quad Core, 1.8GHz)

Memory

4GB RAM+64GB ROM 6GB RAM+128GB ROM (optional)

Display

Canacitive multitouch

Camera

Front: 5MP FF Rear: 16MP AF Rear camera scanning 1D/2D barcode reading

NFC Reader

Type A & B card. Mifare card, Felica card; ISO 15693 compliant

Scanner

Professional scan engine (*optional Zebra & Honeywell)

Speaker

1* 1W

PSAM Card Slot

1* PSAM

Fingerprint Sensor

Capacitive

vSIM

Supports vSIM

Network

2G & 3G & 4G

Wi-Fi

2.4G/5G **IEEE 802.11** a/b/g/n/ac/ax ready

Bluetooth

Bluetooth 5.1

SIM Card Slot

1* Nano SIM

TF Card Slot

1* TF

GPS

GPS/Glonass/Beidou/Galileo Support dual band L1/L5

Power Adapter

Innut: AC 100~240V Output: 5V/3A, 9V/2A

MIC

2* MIC

Buttons

1* Power (lock screen) button

2* Scan button

1* Custom button

Ports

1*Type-c, support OTG 2*pogo pin at the bottom for charging 8* pogo pin on the back for accessories

Battery

Removable polymer lithium battery, 3.8V/5000mAh Non-removable polymer lithium battery, 3.7V/60mAh

Sensor

G-Sensor Proximity sensor Light seńsor Gyroscope E-compass Barometer

Dimensions (L*W*H)

154.4*74.6*17.1mm

Total Weight

245q

Protection

IP67 1.5m drop spec *Certified by a third-party

Environment

Operating temperature: -20°C~55°C Storage temperature:

Accessories (optional)

Single charging base, Charging base, Trigger handle, UHF trigger handle, Hand strap (included) 4-slot charging base, 4-slot battery charger, Protective case, Screen tempered glass